

Textured Paving



Product Information

Castacrete’s textured paving is an alternative to the popular riven finished paving. The process to manufacturing textured paving results in a shot blasted surface exposing the limestone aggregate within the product. This process also adds a durable slip resistant feature. A clean, crisp contemporary look can be achieved using textured paving adding the ever popular stylish modern feel. With having straight sides, this enables you to place the slab side by side without any joints if the contemporary look is being achieved. If a more traditional look is required, then simply add a slight space between each slab, which will accommodate and require finishing off with a jointing product of your choice.



Natural

Dark Grey

Red

Yellow

Cleaning & Maintenance Information regarding the cleaning & maintenance of this product can be requested if required.

Weathering It should be appreciated that with all products weathering and site conditions can cause shade variation to appear across the surface of individual Slabs. This does not in any way affect the performance of the Slabs and any such variation will diminish over a period of time as the product ages.

Efflorescence Any product that contains cement during its early life may exhibit a temporary white discolouration known as efflorescence. This is not a fault with the product and will gradually disappear with exposure to natural elements.

Product Evolution & Appearance Castacrete reserve the right to amend the technical information as deemed necessary and in accordance with the relevant national and international standards without notice. The evolution of new product designs is continuous and information is subject to change without notice please be sure to check with your supplier regarding changes.

Slip/Skid Resistance 55 – Potential for slip - Low

Tolerance on Working Dimensions Thickness +/- 3mm

Tested to: BS EN 1339

	Pack/Size Info	Kg Per Unit	Pieces Per Pack	Kg Per Pack
All colours available	600mm x 600mm 50mm	42.3	24	1015
	600mm x 600mm 35mm	28.0	33	924
	450mm x 450mm 50mm	22.5	46	1035
	450mm x 450mm 35mm	14	68	952
	300mm x 300mm 35mm	7	132	924
	Oakham Pattern 7.2m2			28